



EGF150 Clear Emergency Glazing Film

EGF150 is a self wound, low density polyethylene film with a pressure sensitive adhesive and has been designed to be applied to broken glass prior to replacement. Its application is intended to provide a safety barrier and to help prevent broken glass falling out as well as providing a degree of waterproofing prior to replacement.

SPECIFICATION:

Construction:	Consists of a low density polyethylene film with a rubber based pressure sensitive adhesive on one side.
Colour:	Natural Polyethylene
Film thickness:	0.125mm +/- 0.02mm
Roll size:	1000mm x 20m

Guideline application instructions for EGF150

1. Frame should be clean
2. For small panes, film can be pulled off the roll, cut to size and stuck directly over breakage.
3. For larger panes, peel a few centimetres off the roll and stick to top of frame and simply pull down over the breakage and trim off to desired length.
4. When overlapping on very large panes overlap at least 150mm.
5. Film should be smoothed onto glass so that it is stuck; but not too much pressure should be applied especially where break is jagged.

NB:- IT IS THE PURCHASERS RESPONSIBILITY TO ENSURE THE PRODUCT IS SUITABLE FOR THE INTENDED USE. THE SELLER WILL TAKE NO RESPONSIBILITY FOR DAMAGE TO PERSONS OR PROPERTY RESULTING FROM THE USE OF THIS FILM.