



SOLAR CONTROL FILM

Lower Mirror – Solar Bronze 20

SO-20BR-iSR

Opalux® Lower Mirror Solar Bronze 20 offers a balanced year-round performance of good solar heat rejection with additional winter heat-saving benefits. This architectural film is often used for aesthetic reasons and, while metallised, has a soft bronze exterior appearance.

This Lower Mirror Solar Bronze coloured film is specially metallised to allow plenty of light along with good solar control properties. Avoiding the mirrored look of traditional solar control films, these present a pleasing architectural appearance. It helps to reduce cooling costs and therefore Climate Change Levy liability by lightening the load on air conditioning equipment. Government and business organisations can use Opalux solar control window films as an integral part of seeking to comply with the CRC Energy Efficiency Scheme and The Carbon Trust policies. Opalux® Lower Mirror Solar Bronze 20 is used where a more neutral appearance is required, and are ideally suited to architecturally sensitive applications such as listed buildings. These films achieve good solar heat and glare control and make less visual impact than traditional mirrored films. The film is applied internally and, in daytime, lend the glass a bronze lower mirror outside appearance, whilst from the inside, the visual effect is much less noticeable.

FEATURES

- Good solar heat and glare rejection
- Cuts energy use for cooling
- Lower mirror appearance
- Quick, retro-fit installation
- Scratch-resistant
- Screening of harmful UV rays

BENEFITS

- Alleviate the discomfort caused by excessive heat & glare
- Reducing energy tax liability and contributes to a reduced carbon footprint
- Lower visual impact, especially suited to architecturally sensitive buildings
- Can be used where costly and disruptive large-scale replacement of existing glazing is not a viable option
- Suitable for most non-abrasive window-cleaning

PERFORMANCE DATA		SO-20BR-iSR
SOLAR ENERGY	Transmitted	9%
	Reflected	55%
	Absorbed	39%
VISIBLE LIGHT	Transmitted	17%
	Reflected (Interior)	48%
	Reflected (Exterior)	45%
UV Rejection		99%
Glare Reduction		81%
Shading Coefficient		0.21
Solar Heat Gain Coefficient (G-Value)		0.18
U-Value (W/m²K)		5.3
Total Solar Energy Rejected		82%
Product Warranty		10 years

NOTES

Test results are produced from film applied to 3mm clear single glass. Performance data is subject to change without prior notice. Accurate selection of window films requires specialist knowledge, and it is recommended that specifiers contact the company at the specification stage. It is the users' responsibility to ensure the product is suitable for the intended use. The seller shall not be liable for any direct, indirect or consequential loss or damage howsoever arising.

SPECIFICATION

The solar control window film is to be Opalux® SO-20BR-iSR, as manufactured by Opalux® (www.opaluxwindowfilms.com). The film is to be installed to the interior surface of the glass, and the unique product roll numbers used are to be registered in accordance with the manufacturer's warranty procedure.

An exterior grade alternative is available.
Refer to code: SO-20BR-eSR